LEGAL DESCRIPTION REVIEW CHECKLIST

Descriptions submitted to the Real Property Services Division will not be accepted unless prepared by a professional land surveyor registered in the State of Colorado, and shall conform to the following required criteria:

- 1. Each description shall be typewritten (PDFs are acceptable) on letter size (8.5" x 11.0") plain white paper. Margins shall be a minimum of 1" on the top and 1/2" on the sides and bottom. No paper with company logos will be accepted.
- 2. Metes and bounds descriptions are preferred, lot and block descriptions will be considered on a case by case basis.
- 3. Each description must have an introduction (preamble) which states the proposed use of the property being described (or states: "a parcel of land"), and the Public Land Survey System location of the property (Section, Township, Range, Principal Meridian).
 - a. The preamble should also include City, County, State.
 - b. If the property being described is within a platted subdivision, the name, filing number, and recording information of the subdivision shall be included, as well as the lot and block numbers, if applicable.
 - c. If the property being described is NOT within a platted subdivision, then Identify the document name and recording information, of the subject property.
 - d. A legible copy of the current deed of ownership and/or subdivision plat must be provided with each legal description.
- 4. The point of beginning/commencement shall be tied to an established Public Land Survey System corner (Section, Township, Range, Principal Meridian), or to a monumented point identifiable on a recorded subdivision plat, or property pin (i.e. 3/4" Rebar).
- 5. The area of the property described shall be expressed in both square feet and acres.
- 6. Line information shall include bearings and distances using recognized formats.
- 7. Curve information shall include central (delta) angle, radius, and arc length, if tangent. If non-tangent, the chord or radial bearing shall also be included.
- 8. All distances shall be represented in U.S. survey feet (accounts for the curvature of the earth For my edification).
- Each description shall have a heading similar to "Exhibit A" with subsequent descriptions lettered consecutively (e.g. Exhibit A, Exhibit B, Exhibit C, etc.).
- 10. Each description shall have a basis of bearings statement.
- 11. Each description shall be signed and sealed in accordance with C.R.S. 12-25-217(2).

Illustration Specifications An illustration shall accompany each description and shall conform to the following required criteria:

- 1. Each illustration shall be computer generated on letter size (8.5" x 11.0") plain white paper. Margins shall be a minimum of 1" on the top and 1/2" on the sides and bottom. No paper with company logos will be accepted.
- 2. Each illustration shall use the COA Title Block drawing. There is a link on the RPS webpage for surveyors to download the CAD file with this signature block.
- 3. Each illustration shall include the Public Land Survey System location of the property (Section, Township, Range, Principal Meridian) in the appropriate location at the lower right-hand corner of the aforementioned COA Title Block drawing. If the property being described is within a platted subdivision, the name and filing number shall be included, as well as the lot and block numbers, if applicable.
- 4. Include City, County, and State.
- 5. Each illustration shall note the scale of the drawing (or note if there is no scale), the date, the initials of the drafter and checker, as well as a ROW file number and job number, if applicable, in the appropriate location at the lower left hand corner of the aforementioned COA Title Block drawing.
- Each illustration shall have a north arrow.
- 7. The area of the property described shall be expressed in both square feet and acres.
- 8. Line information shall include bearings and distances.
- 9. Curve information shall include central angle, radius, and arc length using recognized formats, if tangent. If non-tangent, the chord or radial bearing shall also be included.
- 10. All distances shall be represented in U.S. survey feet.
- 11. The point of beginning shall be labeled on metes and bounds descriptions.
 - a. The point of beginning and point of terminus shall be labeled on centerline descriptions.
- 12. All streets, alleys, subdivisions, lots, blocks, parcels, etc. shall be labeled and include all recording information.
- 13. Each illustration shall have a heading similar to "Illustration for Exhibit A" with subsequent illustrations lettered consecutively (e.g. Exhibit A, Exhibit B, Exhibit C, etc.).
- 14. Each illustration shall have the basis of bearings labeled.
- 15. Boundary line of proposed parcel, easement, right-of-way, etc. shall be shown using a solid bold line.
- 16. Existing ownership lines, rights-of-way, section lines, easements, etc., shall be shown using separate and distinct line types (include legend if necessary).
- 17. Each illustration shall include ownership and area, in square feet and acres, of the proposed acquisition.
- 18. Each illustration shall include the following statement: This illustration does not represent a monumented land survey, it is intended only to depict the attached description.
- 19. Each illustration shall be signed and sealed in accordance with C.R.S. 12-25-217(2).